



## DGI printers

This document bridges the gap between Fiery XF documentation and the documentation for following printers:

DGI DR-1904, DGI DR-1904T, DGI NeoJET UV1606, DGI SpaceJET, DGI VistaJet, DGI VTIII-98D, DGI VTIV-62, DGI VTIV-92, DGI XP-2506, DGI XP-2506D, DGI XP-3204T

Refer to the Installation section before you connect the printer to a computer. Refer also to the documentation that was shipped with your printer.

### General Settings

The printer driver supports the printers:

<b>XF Model</b>	<b>Color Modes</b>	<b>Supported OS</b>
DGI DR-1904	4 colors	Win64
DGI DR-1904T	4 colors	Win64, Mac
DGI NeoJET UV1606	4 colors, 6 colors	Win64, Mac
DGI SpaceJET	4 colors	Win64, Mac
DGI VistaJet	4 colors	Win64, Mac
DGI VTIII-98D	4 colors	Win64, Mac
DGI VTIV-62	4 colors, 6 colors	Win64, Mac
DGI VTIV-92	4 colors, 6 colors	Win64, Mac
DGI XP-2506	4 colors, 6 colors	Win64, Mac
DGI XP-2506D	4 colors, 6 colors	Win64, Mac
DGI XP-3204T	4 colors	Win64, Mac

### Installation

Products based on Fiery XF technology: Fiery XF 6.1.1

## Operation

### Color Tools settings

- Printer settings

Each of the supported printers can be configured to operate in the color modes shown in its description.

- Output settings

The “Resolution” and “Print mode” settings are linked. Each time you select a different resolution, the list of possible print modes changes.