EFI[™] Fiery[®] XF and Fiery proServer (client) version 6.3



Fiery Wide Format Products

SYSTEM REQUIREMENTS

| | FIERY XF PRODUCTION VERSION FIERY XF PROOFING VERSION |
|--|--|
| SYSTEM REQUIREMENTS AND RECOMMENDATIONS | |
| Fiery XF Client - Operating Systems | Windows 7/8/8.1/10/2012 Servers (All - 32- & 64-bit supported) |
| | Mac OS X 10.9/10/11/ <mark>12</mark> (All - 32- & 64-bit supported) |
| Fiery XF Client - Hardware Requirements Windows | Dual Core CPU with 2 GHz or more, 3 GB Ram, 10/100 Megabit network controller, 1 available USB port, monitor with |
| | resolution of at least 1280 x 1024 pixels |
| Fiery XF Client - Hardware Requirements Macintosh | Dual Core CPU with 2 GHz or more, 3 GB Ram, 10/100 Megabit network controller, 1 available USB port, monitor with |
| | resolution of at least 1280 x 1024 pixels |
| Fiery XF Server - Operating Systems | Windows 7/8/8.1/10/2008 R2/2012 Servers (All - 64-bit only) Mac OS |
| | X 10.9/10/11 <mark>/12</mark> (All 32- & 64-bit, running in 32-bit mode) |
| Fiery XF Server - Hardware Requirements Windows | Quad Core CPU with 2 GHz or more, 8 GB RAM, 300 GB HDD, 10/100 Megabit network controller, 2 available USB ports |
| Fiery XF Server - Hardware Recommendations Windows | LCD display with 1920 x 1080 pixels or more; 3 GHz 8-Core (or faster / more cores) processor; 32GB RAM; 1 Gigabit LAN |
| | controller; 4x 3.5", Serial-ATA, 1.500 TB - Ideally 4 hard drives should be routed via "Server File Maintenance" in the Fiery |
| | XF Control as follows: 1 hard drive for the operating system, Fiery XF and the temporary folder; 1 hard drive for the job |
| | folder; 2 hard drives connected via Raid 0 for the output folder |
| Fiery XF Server - Hardware Requirements Macintosh | Macintosh MacTel (native), Quad Core CPU with 2 GHz or more, 8 GB RAM, 300 GB HDD, 10/100 Megabit network |
| | controller, 2 available USB ports |
| Fiery XF Server - Hardware Recommendations Macintosh | Mac Pro Configuration: "3.33 GHz 6-Core Intel Xeon Westmere" (or faster / more cores); 32GB RAM; 1 Gigabit LAN |
| | controller; Mac Pro RAID Card; 4 x 1 TB 3 GBit/Sec. Serial-ATA - Ideally 4 hard drives should be routed via "Server File |
| | Maintenance" in the Fiery XF Control as follows: 1 hard drive for the operating system, Fiery XF and the temporary folder, |
| | 1 hard drive for the job folder, 2 hard drives connected via Raid 0 for the output folder |
| EFI Cut Server - Operating Systems | Windows® 8, Windows 7®, Windows 2008 Server, a monitor resolution for the client of 1280 x 1024 is recommended. |
| EFI Cut Server - Hardware Requirements | 2 GHz Pentium IV PC or higher, 1 GB Ram per CPU, 60 GB HDD, 10/100 MBit Network |
| Layout Option - Hardware Requirements and Supported | Operating System: Windows® 8, Windows® 7, Hardware Requirements: Dual Core CPU with 2 GHz or more, 4 GB |
| File Formats | RAM, 60 GB HDD, File Formats: PDF, imageEPS, PSD, JPEG, Tiff - in CMYK and Grey |
| Softproof Option - Hardware Requirements | Operating System: Windows® 8, Windows® 7, Hardware Requirements: Dual Core CPU with 2 GHz or more, 2 GB RAM, 500 GB HDD, 10/100 Mbit Network, 1 available USB port, DVI connection with at least, 1.920x1.200 pixel and 24 |